

## Gigaset 2000 S

Mobile Unit for operation at  
DECT-base stations

**Standards:** DECT  
GAP  
(Generic Access Profile)



### Main features:

- Full functionality with base stations of the Gigaset 2000 and Gigaset 1000 family
- Normal dialling
- Block dialling (input of dial number before trunk line seizure) with correction facility
- Last number redial of 5 last different dialling numbers
- Memory for 10 abbreviated dialling numbers
- ON / OFF / PROTECT-mode
- Automatic „switch to line“ at pick up of handset from base station or charging unit (adjustable)
- Automatic „release of line“ on replacing handset
- Three volume levels
- 3 - tone ringer (ringer volume and pitch programmable in 6 levels)
- Key confirmation tone, warning tones for low battery, limit of radio range
- NiCd and NiMH batteries may be used
- Elektronik lock
- (Protection by PIN-Code)
- Direct call function
- Emergency call function
- Voice encoding (DECT encryption)
- Multiple registration of mobile units at max. 4 base stations
- Handset with 16-character display and icons, with battery condition display
- Power supply:  
2 rechargeable batteries (type AA)
- Operation time:  
- 7 hours (NiCd), 13 hours (NiMH 1300mA) continuous operation  
- 70 hours (NiCd),  
130 hours (NiMH 1300 mA) standby
- Dimensions:  
ca. 160x55x28 mm (LxWxD)
- Weight including batteries:  
approx. 165g