

Gigaset 3060 isdn

Interface, Connection, Standards,

- **Interface:** S₀ (DSS1-protocol)
- **Connection:** PSTN / PBX
- **Standards:** DECT / GAP / Euro-ISDN

Positioning

Cordless digital telephone system for 1 Euro-ISDN Basic Rate Interface for up to 8 mobile handsets and 2 analogue equipments

Configuration

- Basestation for 1 Euro-ISDN Basic Rate Interface
- Connection configuration point-to-point or point-to-multipoint
- Connectable to PSTN- or PABX-lines
- Up to 8 handsets (Classic and Comfort handsets)
- Internal corded lines for conventional devices such as telephone, facsimile, answering machine, modem, door communication

System features

- External / internal connections (max. 2/ 4)
- Call access rights unrestricted, receive only, internal
- Encoding of the air-interface
- Programming of system
- Automatic selection of pulse or DTMF dialing at the internal connection
- Door communication and control
- Line access automatic or manual
- Indication of call charge sum per base station, per subscriber or per multiple subscriber number
- Call allocation collective or group call
- 3 different ringing tones: external, internal, door station
- Call rejection
- Call waiting and call waiting rejection



System features

- Calling and connected line identification (indication of name, if programmed in the telephone book of the comfort handset)
- Calling and connected line identification restriction
- Direct dialing in
- Free MSN choice at outgoing calls
- Missed calls list with 10 entries
- Call hold for external calls
- Call on hold toggling
- Call transfer of internal calls
- Automatic recall if call transfer not successful
- Three party conference
- Call park of external calls
- Call pick-up
- Call pick-up from a connected answering machine
- Call forwarding
- Automatic recall (external)
- Keypad-protocol
- Call waiting

- Phone number lock per subscriber
- Electronic locking / 3 emergency numbers
- Selective call-release
- DTMF-controlling, e.g. answering machine at the internal connection

Gigaset 3060 isdn

System features

- Registration of handsets at up to 4 base stations (with Gigaset 3000 Comfort)
- Seamless handover of external calls by Gigaset Repeater
- Indication of the base station number by the handset display

With Gigaset 3000 Comfort

- Handsfree function
- Simple call by call via NET key
- Automatic call repetition

Miscellaneous

- Wall mounting
- Dimensions: ca.175 x 182 x 35 mm
- LED in base station
- External AC/DC-adaptor

Packaging

- 1 Gigaset 3060isdn
- 1 Gigaset 3000 Comfort handset
- 1 Gigaset 3000 L charging unit

Market Introduction

- September 99 in midnightblue