

# SIEMENS

## Gigaset 3075 isdn

### Interface, Connection, Standards

- Interface: S<sub>0</sub> (DSS1-protocol)
- Connection: Euro-ISDN basic rate access and behind PBX
- Standards: DECT / GAP / Euro-ISDN/DPRS (as of 10/00)

### Configuration

- Connection to Euro-ISDN basic rate access
- 8 cordless subscribers
- Registration of mobile units at up to 4 base stations
- 2 analogue jacks for telephone, fax, answering machine, modem, door station
- Corded PC access through USB port via Gigaset M105 Data (starting 07/00)
- Cordless PC access through V.24 port via Gigaset M101 Data
- Multi-cell capable



### System features

- Installation assistant (plug & play)
- External- / internal calls simultaneously (Max. 2 / 4)
- Pre-Selection of providers
- Missed calls list with 20 entries
- Night service
- Call allocation for collective call, group call, call waiting, internal call, door station
- Ringer tone per MSN programmable
- Call barring features:
  - individual call barring per internal subscriber
  - system clock
- Call access rights per MSN (full / incoming / internal)
- Display of call duration / call charges
- Call charge management per MSN / subscriber / base

### System features

- Call pickup (same call allocation)
- Call hold / consultation
- Internal call transfer of external calls
- Call back when call transfer not successful
- System programming
- Copy of phonebook among comfort mobile units
- DTMF remote control e.g. of connected answering machine
- Call forwarding via 2nd B-channel
- Music on hold (disconnectible)
- Programming international and area code
- Centrex features (MWI, DR, CNI)
- Keypad dialing (also automatic)
  - \* / # dialing
- DTMF-CLIP for analogue access (number display)
- DTMF dial method at analogue access
- Door station control via door station adapter

# SIEMENS

## Gigaset 3075 isdn

### ISDN supplementary features

- Administration of up to 10 MSNs
- Clock feature with synchronisation via ISDN
- MSN selection at outgoing calls
- Direct dialing in (MSN)
- MSN-display of caller and called party (CLIP, COLP)
- MSN-display restriction (CLIR, COLR)
- Call hold / consultation / toggling (CH)
- Three party conference (3PTY)
- Call charge display (AOC)
- Parking of external calls (TP)
- Call waiting and its rejection (CW)
- Call forwarding, call deflection (CF/CD)
- Automatic call back (CCBS)
- Malicious call identification (MCID)
- Support of Repeater

### PC applications

- PC link between cordless and corded PC-access
- Corded internet / remote LAN access via USB port under Windows 98
- Cordless internet / remote LAN access via V.24 port under Windows 95/98 and NT 4.0/WIN 2000
- Configuration / charge management
- SW Update / upgrade via PC
- CTI (Computer-telephony integration):
  - Connection via ,talk & surf' software
  - Configuration of base station via USB or V.24 port
  - ISDN features available via ,communication circle
- Faxemulation
- Least cost routing by PC-table

### Built-in answering machine

- Multiple areas (3 MSN)
- Recording capacity ca. 35 min
- User guiding via announcements
- Predefined announcements (plug & play)
- Number display with direct redial feature
- Display of new messages with direct access
- Display of the number of new / all messages
- Monitoring of messages to called parties
- Locking of answering machine by own PIN
- Unlimited memos and 2 announcements available
- Monitoring of calls
- Call pickup from answering machine
- Remote access via mobile units
- Announcement of date / time per message
- Date / time per MSN and message
- Memo feature
- Unlimited data retention

### Miscellaneous

- Desktop and wallmounted base station
- LED in base station for display of operation / registration, ISDN-line status
- Base station (LxWxH) ca. 208x173x74 mm
- External power unit